



Multi-Door Reach-In Refrigerators

Double-Door Models: COR40RRTMD,
COR48RRTMD and COR49RRBMD

Triple-Door Model: COR74RRTMT

COR40RRTMD



Standard Features

- External temperature display and power indicator
- Foamed-in-place with high-density, CFC-free polyurethane insulation
- All doors are 24ga 304 #3 stainless steel
- Heavy-duty epoxy shelves
- Robust body construction
- Aluminum interior
- 10' (3 m) long power cord
- R-134a refrigerant, CFC free

COR40RRTMD Special Features

- 6" (15.2 cm) casters
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint

COR48RRTMD



COR48RRTMD and COR74RRTMT

Special Features

- External Monitor Control Panel includes temperature display, power indicator, door ajar indicator and condensate eliminator switch
- Cylinder lock and recessed handle
- 6" (15.2 cm) casters
- Stainless steel finish on exterior side walls

COR49RRBMD Special Features

- Stainless steel front, top and bottom covers
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint
- Fan motors: sealed, cast iron oil filled with life expectancy of 10 years

COR49RRBMD



COR74RRTMT





Multi-Door Reach-In Refrigerators

Technical Specifications

	COR40RRTMD	COR48RRTMD	COR49RRBMD	COR74RRTMT
Operating Dimensions				
Height	78.5" (199.4 cm)	82.5" (209.6 cm)	78" (198.1 cm)*	82.5" (209.6 cm)
Width	46.6" (118.4 cm)	56.5" (143.5 cm)	60" (152.4 cm)	84.8" (215.4 cm)
Depth	31.5" (80 cm)	33.8" (85.9 cm)	29.5" (74.9 cm)	33.8" (85.9 cm)
Specifications				
Door type	Swing	Swing	Swing	Swing
Capacity	37.6 cubic ft (1064 ltr)	50 cubic ft (1415 ltr)	49 cubic ft (1388 ltr)	76.7 cubic ft (2171 ltr)
Shelves	6	6	8	9
Compressor	1/3 hp	1/2 hp	1/3 hp	1/2 hp
Amperage	9	10	9.9	12.8
Temperature range	32-39°F (0-4°C)	32-39°F (0-4°C)	32-39°F (0-4°C)	32-39°F (0-4°C)
Refrigerant type	R-134a	R-134a	R-134a	R-134a
Wall thickness	2.3" (5.8 cm)	2.5" (6.4 cm)	2.3" (5.8 cm)	2.5" (6.4 cm)
Condensing unit	Top mount	Top mount	Bottom mount	Top mount
Shipping Dimensions				
Height	75.5" (191.8 cm)	79" (200.7 cm)	81.8" (207.8 cm)	79" (200.7 cm)
Width	48.8" (32.5 cm)	60" (152.4 cm)	60.6" (153.9 cm)	90" (228.6 cm)
Depth	33" (83.8 cm)	38.5" (97.8 cm)	30.1" (76.4 cm)	38.5" (97.8 cm)
Gross weight	366 lb (166 kg)	474 lb (215 kg)	445 lb (202 kg)	603 lb (274 kg)
Units per 20' container	14	8	11	6
Units per 40' container	NA	NA	22	NA
Units per 45' container	26	17	NA	11

*Height does not include leveling legs, which can be adjusted up to 1" (2.5 cm).

Optional Equipment: Additional shelves, Casters for COR49RRBMD

Agency Listings:



Ordering Information

Model Number	Part Number	Description
COR40RRTMD	400000018	RRTMD 40CU TPMT SW/DR2 120/60HZ
COR48RRTMD	400000015	RRTMD 48CU TPMT SW/DR2 120/60HZ
COR49RRBMD	400000013	RRBMD 49CU BTMT SW/DR2 120/60HZ
COR74RRTMT	400000016	RRTMT 74CU TPMT SW/DR3 120/60HZ



For more information
or to place an order,
contact your sales
representative or
authorized distributor.

Phone: 1-800-238-3600
Fax: 1-800-535-4235

www.cornelius.com