



Single-Door Reach-In Refrigerators

Models COR20RRTM, COR22RRTM
and COR23RRBM

COR20RRTM



Standard Features

- External temperature display and power indicator
- Foamed-in-place with high-density, CFC-free polyurethane insulation
- All doors are 24ga 304 #3 stainless steel
- Heavy-duty epoxy shelves
- Robust body construction
- Aluminum interior
- 10' (3 m) long power cord
- R-134a refrigerant, CFC free

COR20RRTM Special Features

- 6" (15.2 cm) casters
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint

COR22RRTM



COR22RRTM Special Features

- External Monitor Control Panel includes temperature display, power indicator, door ajar indicator and condensate eliminator switch
- Cylinder lock and recessed handle
- 6" (15.2 cm) casters
- Stainless steel finish on exterior side walls

COR23RRBM



COR23RRBM Special Features

- Solid door with exterior stainless steel finish
- Stainless steel front, top and bottom covers
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint
- Fan motors: sealed, cast iron oil filled with life expectancy of 10 years



Single-Door Reach-In Refrigerators

Technical Specifications

	COR20RRTM	COR22RRTM	COR23RRBM
Operating Dimensions			
Height	78.5" (199.4 cm)	82.5" (209.6 cm)	78" (198.1 cm)*
Width	23" (58.4 cm)	28.3" (71.9 cm)	30" (76.2 cm)
Depth	31.5" (80 cm)	33.8" (85.9 cm)	29.5" (74.9 cm)
Specifications			
Door type	Swing	Swing	Swing
Capacity	20 cubic ft (566 ltr)	22.2 cubic ft (628 ltr)	23 cubic ft (651 ltr)
Shelves	3	3	4
Compressor	1/3 hp	1/3 hp	1/4 hp
Amperage	7	6.6	8.5
Temperature range	32-39°F (0-4°C)	32-39°F (0-4°C)	32-39°F (0-4°C)
Wall thickness	2.3" (5.8 cm)	2.5" (6.4 cm)	2.3" (5.8 cm)
Condensing unit	Top mount	Top mount	Bottom mount
Refrigerant type	R-134a	R-134a	R-134a
Shipping Dimensions			
Height	75.5" (191.8 cm)	79" (200.7 cm)	81.8" (207.8 cm)
Width	26" (66 cm)	30" (76.2 cm)	30.6" (77.7 cm)
Depth	33" (83.8 cm)	38.5" (97.8 cm)	30.1" (76.4 cm)
Gross weight	252 lb (114 kg)	280 lb (127 kg)	317 lb (144 kg)
Units per 20' container	22	18	21
Units per 40' container	NA	NA	45
Units per 45' container	40	34	NA

*Height does not include leveling legs, which can be adjusted up to 1" (2.5 cm).

Optional Equipment: Additional shelves, Casters for COR23RRBM

Agency Listings:



Ordering Information

Model Number	Part Number	Description
COR20RRTM	400000017	RRTM 20CU TPMT SW/DR 120/60HZ
COR22RRTM	400000014	RRTM 22CU TPMT SW/DR 120/60HZ
COR23RRBM	400000012	RRBM 23CU BTMT SW/DR 120/60HZ



For more information or to place an order, contact your sales representative or authorized distributor.

Phone: 1-800-238-3600
Fax: 1-800-535-4235

www.cornelius.com