



Single-Door Reach-In Freezers

Models COR20RFTM, COR22RFTM
and COR23RFBM

COR20RFTM



Standard Features

- External temperature display and power indicator
- Foamed-in-place with high-density, CFC-free polyurethane insulation
- All doors are 24ga 304 #3 stainless steel
- Heavy-duty epoxy shelves
- Robust body construction
- Aluminum interior
- 10' (3 m) long power cord
- R-134a refrigerant, CFC free

COR20RFTM Special Features

- 6" (15.2 cm) casters
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint

COR22RFTM



COR22RFTM Special Features

- External Monitor Control Panel includes temperature display, power indicator, door ajar indicator and condensate eliminator switch
- Cylinder lock and recessed handle
- 6" (15.2 cm) casters
- Stainless steel finish on exterior side walls

COR23RFBM



COR23RFBM Special Features

- Solid door with exterior stainless steel finish
- Stainless steel front, top and bottom covers
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint



Single-Door Reach-In Freezers

Technical Specifications

	COR20RFTM	COR22RFTM	COR23RFBM
Operating Dimensions			
Height	78.5" (199.4 cm)	82.5" (209.6 cm)	78" (198.1 cm)*
Width	23" (58.4 cm)	28.3" (71.9 cm)	30" (76.2 cm)
Depth	31.5" (80 cm)	33.8" (85.9 cm)	29.5" (74.9 cm)
Specifications			
Door type	Swing	Swing	Swing
Capacity	20 cubic ft (566 ltr)	22.2 cubic ft (628 ltr)	23 cubic ft (651 ltr)
Shelves	3	3	4
Compressor	1/3 hp	1/3 hp	1/2 hp
Amperage	7.5	10	8.5
Temperature range	-10 - 0°F (-23 - 18°C)	-10 - 0°F (-23 - 18°C)	-10 - 0°F (-23 - 18°C)
Wall thickness	2.3" (5.8 cm)	2.5" (6.4 cm)	2.3" (5.8 cm)
Condensing unit	Top mount	Top mount	Bottom mount
Refrigerant type	R-404a	R-404a	R-404a
Shipping Dimensions			
Height	75.5" (191.8 cm)	79" (200.7 cm)	81.8" (207.8 cm)
Width	26" (66 cm)	30" (76.2 cm)	30.6" (77.7 cm)
Depth	33" (83.8 cm)	38.5" (97.8 cm)	30.1" (76.4 cm)
Gross weight	257 lb (117 kg)	283 lb (128 kg)	323 lb (147 kg)
Units per 20' container	22	18	21
Units per 40' container	NA	NA	45
Units per 45' container	40	34	NA

*Height does not include leveling legs, which can be adjusted up to 1" (2.5 cm).

Optional Equipment: Additional shelves, Casters for COR23RFBM

Agency Listings:



Ordering Information

Model Number	Part Number	Description
COR20RFTM	400000024	RFTM 20CU TPMT SW/DR 120/60HZ
COR22RFTM	400000021	RFTM 22CU TPMT SW/DR 120/60HZ
COR23RFBM	400000019	RFBM 23CU BTMT SW/DR 120/60HZ



For more information
or to place an order,
contact your sales
representative or
authorized distributor.

Phone: 1-800-238-3600
Fax: 1-800-535-4235

www.cornelius.com