



Multi-Door Reach-In Freezers

Double-Door Models: COR40RFTMD,
COR48RFTMD and COR49RFBMD

Triple-Door Model: COR74RFTMT

COR40RFTMD



Standard Features

- External temperature display and power indicator
- Foamed-in-place with high-density, CFC-free polyurethane insulation
- All doors are 24ga 304 #3 stainless steel
- Heavy-duty epoxy shelves
- Robust body construction
- Aluminum interior
- 10' (3 m) long power cord
- R-134a refrigerant, CFC free

COR40RFTMD Special Features

- 6" (15.2 cm) casters
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint

COR48RFTMD



COR48RFTMD and COR74RFTMT

Special Features

- External Monitor Control Panel includes temperature display, power indicator, door ajar indicator and condensate eliminator switch
- Cylinder lock and recessed handle
- 6" (15.2 cm) casters
- Stainless steel finish on exterior side walls

COR49RFBMD Special Features

- Stainless steel front, top and bottom covers
- Exterior side walls are constructed of 24ga G90 galvanized pre-painted steel with aluminum-colored polyester paint
- Fan motors: sealed, cast iron oil filled with life expectancy of 10 years

COR49RFBMD



COR74RFTMT





Multi-Door Reach-In Freezers

Technical Specifications

	COR40RFTMD	COR48RFTMD	COR49RFBMD	COR74RFTMT
Operating Dimensions				
Height	78.5" (199.4 cm)	82.5" (209.6 cm)	78" (198.1 cm)*	82.5" (209.6 cm)
Width	46.6" (118.4 cm)	56.5" (143.5 cm)	60" (152.4 cm)	84.8" (215.4 cm)
Depth	31.5" (80 cm)	33.8" (85.9 cm)	29.5" (74.9 cm)	33.8" (85.9 cm)
Specifications				
Door type	Swing	Swing	Swing	Swing
Capacity	37.6 cubic ft (1064 ltr)	50 cubic ft (1415 ltr)	49 cubic ft (1388 ltr)	76.7 cubic ft (2171 ltr)
Shelves	6	6	8	9
Compressor	1/2 hp	1/2 hp	1 hp	3/4 hp
Amperage	12	12	10	7.37
Temperature range	-10 - 0°F (-23 - 18°C)	-10 - 0°F (-23 - 18°C)	-10 - 0°F (-23 - 18°C)	-10 - 0°F (-23 - 18°C)
Wall thickness	2.3" (5.8 cm)	2.5" (6.4 cm)	2.3" (5.8 cm)	2.5" (6.4 cm)
Condensing unit	Top mount	Top mount	Bottom mount	Top mount
Refrigerant type	R-404a	R-404a	R-404a	R-404a
Shipping Dimensions				
Height	75.5" (191.8 cm)	79" (200.7 cm)	81.8" (207.8 cm)	79" (200.7 cm)
Width	48.8" (32.5 cm)	60" (152.4 cm)	60.6" (153.9 cm)	90" (228.6 cm)
Depth	33" (83.8 cm)	38.5" (97.8 cm)	30.1" (76.4 cm)	38.5" (97.8 cm)
Gross weight	386 lb (175 kg)	479 lb (217 kg)	445 lb (202 kg)	658 lb (298 kg)
Units per 20' container	14	8	11	6
Units per 40' container	NA	NA	22	NA
Units per 45' container	26	17	NA	11

*Height does not include leveling legs, which can be adjusted up to 1" (2.5 cm).

Optional Equipment: Additional shelves, Casters for COR49RFBMD

Agency Listings:



Ordering Information

Model Number	Part Number	Description
COR40RFTMD	400000025	RFTMD 40CU TPMT SW/DR2 120/60HZ
COR48RFTMD	400000022	RFTMD 48CU TPMT SW/DR2 120/60HZ
COR49RFBMD	400000020	RFBMD 49CU BTMT SW/DR2 120/60HZ
COR74RFTMT	400000023	RFTMT 74CU TPMT SW/DR3 120/60HZ



For more information
or to place an order,
contact your sales
representative or
authorized distributor.

Phone: 1-800-238-3600
Fax: 1-800-535-4235

www.cornelius.com