



Sandwich Prep Tables

Models COR278SPT, COR4512SPTD
and COR5916SPTD



COR278SPT



COR4512SPTD



COR5916SPTD

Features

- All stainless steel exterior front, top, and sides for more durability and greater appearance
- Exterior bottom and rear are galvanized steel
- Aluminum interior prevents corrosion
- Cutting board on top provides a tough surface for a comfortable working area
- Self-closing doors with safety stop at 120 degrees
- Heavy-duty, chrome-plated hinges
- Hermetic seal with a vinyl magnetic gasket keyed into a thermal breaker.
- Recessed handles
- Casters enhance mobility
- Adjustable wire shelves and clear plastic salad pans
- Bumpers on the back of the cooler provide protection
- Extra-dense, foamed-in-place polyurethane insulation provides solid structure and low energy consumption
- Wall thickness averages 2" (5.1 cm)
- Forced air refrigeration system permits rapid pull down and balanced temperature throughout the whole cabinet interior
- Guided air flow provides excellent circulation under pans
- R-134a refrigerant, CFC free
- Self contained
- Simple installation
- Complies with NSF standard 7
- UL listed



Sandwich Prep Tables

Technical Specifications

	COR278SPT	COR4512SPTD	COR5916SPTD
Operating Dimensions			
Height	41.7" (105.9 cm)	41.7" (105.9 cm)	41.7" (105.9 cm)
Width	27.5" (69.9 cm)	45" (114.3 cm)	59" (149.9 cm)
Depth	30.4" (77.2 cm)	30.4" (77.2 cm)	30.4" (77.2 cm)
Specifications			
Door type	Swing	Swing	Swing
Capacity	6.6 cubic ft (198 ltr)	11.6 cubic ft (340 ltr)	15.7 cubic ft (453 ltr)
Shelves	2	4	4
Compressor	1/5 hp	1/4 hp	1/3 hp
Amperage	4.5	7	8.5
Temperature range	33-41°F (0.5-5°C)	33-41°F (0.5-5°C)	33-41°F (0.5-5°C)
Refrigerant type	R-134a	R-134a	R-134a
Shipping Dimensions			
Height	42" (106.7 cm)	42" (106.7 cm)	42" (106.7 cm)
Width	30.4" (77.2 cm)	47.8" (121.4 cm)	61" (154.9 cm)
Depth	34" (86.4 cm)	34" (86.4 cm)	34" (86.4 cm)
Gross weight	220 lb (100 kg)	311 lb (141 kg)	362 lb (164 kg)
Units per 20' container	36	20	14
Units per 40' container	78	44	30

Optional Equipment: Additional shelves

Agency Listings:



Ordering Information

Model Number	Part Number	Description
COR278SPT	400000026	SPT 8CU 27W SW/DR 120/60HZ
COR4512SPTD	400000027	SPT D 12CU 45W SW/DR2 120/HZ
COR5916SPTD	400000028	SPT D 16CU 59W SW/DR2 120/60HZ



For more information
or to place an order,
contact your sales
representative or
authorized distributor.

Phone: 1-800-238-3600
Fax: 1-800-535-4235

www.cornelius.com