



Bottle Coolers

Models COR5014UBCSD, COR6519UBCSD
and COR9530UBCST



COR5014UBCSD



COR6519UBCSD



COR9530UBCST

Features

- Black pre-painted steel exterior
- Stainless steel counter top and lids enhance durability
- Exterior bottom is galvanized steel
- Galvanized steel interior offers ample storage space for refrigerated bar products
- Stainless steel glass stop for dishware handling
- Rubber handles
- Bottle opener and cap catcher (COR9530UBCST on both front corners)
- Interior bin divider system
- Bumpers on the back of the cooler provide protection
- Fully sealed galvanized steel base to prevent dirt accumulation underneath the unit
- Extra-dense, foamed-in-place polyurethane insulation provides solid structure and low energy consumption
- Wall thickness averages 2" (5.1 cm)
- Forced-air refrigeration system permits rapid pull-down and balanced temperature throughout the cabinet interior
- R-134a refrigerant, CFC free
- Self contained
- Simple installation
- Complies with NSF standard 7
- UL listed



Bottle Coolers

Technical Specifications

	COR5014UBCSD	COR6519UBCSD	COR9530UBCST
Operating Dimensions			
Height	34.3" (87 cm)	34.3" (87 cm)	34.3" (87 cm)
Width	52.3" (132.7 cm)	66.8" (169.6 cm)	97.8" (248.3 cm)
Depth	27.5" (69.9 cm)	27.5" (69.9 cm)	27.5" (69.9 cm)
Specifications			
Door type	Slide	Slide	Slide
Shelves	2	3	4
Capacity	14 cubic ft (397 ltr)	19 cubic ft (538 ltr)	30 cubic ft (850 ltr)
Compressor	1/4 hp	1/3 hp	1/3 hp
Amperage	6.7	8.7	8.7
Temperature range	33-40°F (0.5-4°C)	33-40°F (0.5-4°C)	33-40°F (0.5-4°C)
Refrigerant type	R-134a	R-134a	R-134a
Shipping Dimensions			
Height	40.5" (102.9 cm)	40.5" (102.9 cm)	40.5" (102.9 cm)
Width	55" (139.7 cm)	69.8" (177.3 cm)	101" (256.5 cm)
Depth	30.3" (77 cm)	30.3" (77 cm)	30.3" (77 cm)
Gross weight	293 lb (133 kg)	344 lb (156 kg)	465 lb (211 kg)
Units per 20' container	24	18	12
Units per 40' container	50	38	24

Agency Listings:



Ordering Information

Model Number	Part Number	Description
COR5014UBCSD	400000032	UBC D 14CU 52W SL/DR2 120/60HZ
COR6519UBCSD	400000033	UBC D 19CU 66W SL/DR2 120/60HZ
COR9530UBCST	400000034	UBC T 30CU 97W SL/DR3 120/60HZ



For more information or to place an order, contact your sales representative or authorized distributor.

Phone: 1-800-238-3600
Fax: 1-800-535-4235

www.cornelius.com