



Draft Beer Dispensers

Models COR10DBD1DT and COR15DBD2DT



COR10DBD1DT



COR15DBD2DT

Features

- Black pre-painted steel exterior
- Stainless steel counter provides space for food and beverage handling
- Galvanized steel interior offers ample storage space for beer kegs
- Overflow drain located on counter top
- Stainless steel interior floor enhances durability
- Self-closing doors with safety stop at 120 degrees
- Heavy-duty, chrome-plated hinges
- Hermetic seal with a vinyl magnetic gasket keyed into a thermal breaker
- Recessed handles
- Door locks
- Bumpers on the back of the cooler provide protection
- Fully sealed galvanized steel base to prevent dirt accumulation underneath the unit
- Casters enhance mobility (Standard on COR10DBD1DT and optional for COR15DBD2DT)
- Extra-dense, foamed-in-place polyurethane insulation provides solid structure and low energy consumption
- Wall thickness averages 2" (5.1 cm)
- Forced-air refrigeration system permits rapid pull-down and balanced temperature throughout the cabinet interior
- R-134a refrigerant, CFC free
- Self contained
- Simple installation
- Complies with NSF standard 18
- UL listed



Draft Beer Dispensers

Technical Specifications

	COR10DBD1DT	COR15DBD2DT
Operating Dimensions		
Height	56.5" (143.5 cm)	51.5" (130.8 cm)
Width	25.3" (64.3 cm)	56.3" (142.9 cm)
Depth	33.3" (84.6 cm)	24" (61 cm)
Specifications		
Door type	Swing	Swing
Capacity	9.8 cubic ft (283 ltr)	14.5 cubic ft (425 ltr)
Compressor	1/5 hp	1/3 hp
Amperage	4.7	8.2
Temperature range	33-40°F (0.5-4°C)	33-40°F (0.5-4°C)
Refrigerant type	R-134a	R-134a
Shipping Dimensions		
Height	43.5" (110.5 cm)	41.5" (105.4 cm)
Width	38" (96.5 cm)	59.5" (151.1 cm)
Depth	27.3" (69.3 cm)	27.6" (70.1 cm)
Gross weight	230 lb (104 kg)	341 lb (155 kg)
Units per 20' container	36	22
Units per 40' container	72	48

Optional Equipment: Additional shelves, Casters for COR15DBD2DT

Agency Listings:



Ordering Information

Model Number	Part Number	Description
COR10DBD1DT	400000030	DBD 1DT 10CU 1DT SW/DR 120/60HZ
COR15DBD2DT	400000031	DBD 2DT 15CU 2DT SW/DR2 120/60HZ



For more information
or to place an order,
contact your sales
representative or
authorized distributor.

Phone: 1-800-238-3600
Fax: 1-800-535-4235

www.cornelius.com